Natural Paving is supplied by Talasey Ltd,

St Vincents House, Normanby Road, Scunthorpe,
DN15 8QT

# DECLARATION OF PERFORMANCE

Cinder NSBP Mixed Calibrated Project Pack

**1. Product Type**: Quartzitic Sandstone

**2 Unique Identification Code(s):** NPPCINSBPMx-PP

**3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**
Commercial And Domestic Paving For External Use

**4. Manufacturer:** Natural Paving Products (UK) Ltd. (Stone Exporters (India) Pvt Ltd.)
Bhudpura
India

**5. Authorised Representative**: Steve Milburn

**6. System of System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:** Level 4

**7. Harmonised Standard:** EN1341:2012

**8. Notified Body:** N/A

**9. Declared Performance**

| Essential Characteristic | Performance | Harmonised Technical Specification EN1341:2012 |
|---|---|---|
| Release Of Dangerous Substances | NPD | 4.11 |
| Compressive Strength - Lowest Expected Value | 58.4MPa | EN1926 4.4 |
| Slip Resistance Wet Value | 51 | EN14231 4.6.1 |
| Slip Resistance Dry Value | 61 | EN14231 4.6.1 |
| Skid Resistance | NPD | 4.6.2 |
| Freeze/Thaw Resistance – Mean values before and after freeze/thaw test | 115.9/112.7MPa | EN12371 4.3.1 |
| Freeze/Thaw Resistance – De-icing salts | NPD | 4.3.2 |
| Polishing In Use | NPD | 4.6.3 |
| Water Absorption | 1.6% | EN13755 |
| Abrasion Resistance | 17.5mm | EN14157 |

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

**Name and function:** Mark Wall, Managing Director

**Place and date of issue:**
Belton Road
Sandtoft
Doncaster
North Lincolnshire
DN8 5SX

31st March 2016

**Signature:** 